

MANUFACTURER:

SaverSystems
800 S 7th St.
Richmond, IN 47374
800-860-6327
www.1deck.com



DESCRIPTION

#1 Deck Premium Fence Stain is an advanced, water-based, semi-transparent stain formulation designed to penetrate deep into wood pores for maximum protection and longevity. It protects wooden fences from harmful UV rays and damage caused by water penetration. #1 Deck Premium Fence Stain is safe to use, has a low odor, and is easy to clean up with soap and water. It is ideal for all wood types other than composite lumber.

WHERE TO USE

#1 Deck Premium Fence Stain is intended for all exterior, weathered, vertical wood surfaces including fences and wood siding. It can be used on all wood types including pine, cedar, redwood, and more.

ADVANTAGES

- Both a stain and sealer for your wood
- Protects wood from damaging UV rays
- Available in 5 beautiful semi-transparent finishes – Natural, Cedar, Light Walnut, Dark Walnut, & Driftwood Gray
- For use on all wood types
- Dries to a flat, natural looking finish
- Water-based, easy cleanup
- Low VOC content (<50 g/L)

SURFACE PREPARATION

NEW WOOD

Allow new wood to weather for 3-6 months.

- **Step 1:** Clean wood with #1 Deck Wood Cleaner. Rinse wood thoroughly with a garden hose or pressure washer (max. 1200 PSI).
- **Step 2:** Brighten and neutralize wood with #1 Deck Wood Brightener and rinse thoroughly with a garden hose.

Note: For oily wood types, such as cedar or redwood, we recommend allowing the wood to weather for 1 year to improve penetration. Applying stain to these surfaces could result in unsatisfactory results if the surface has not weathered sufficiently for the stain to penetrate.

Limitations: While this product can be used on both vertical and horizontal wood surfaces such as decks, the 3 year guarantee is applicable only to vertical surfaces. When using

on dense, less porous products like mahogany, ipe or other exotic hardwoods, maintenance coats will be required on a more frequent basis.

WEATHERED OR GRAY WOOD

- **Step 1:** Clean wood with #1 Deck Wood Cleaner and rinse thoroughly with a garden hose or pressure washer (max. 1200 PSI).
- **Step 2:** Brighten and neutralize wood with #1 Deck Wood Brightener and rinse thoroughly with a garden hose.

PREVIOUSLY STAINED WOOD

Do not use #1 Deck Premium Fence Stain over solid stains, painted, or varnished surfaces. These surfaces must be stripped prior to application of the product. If sanding is necessary to remove old finishes, use a coarse grit sandpaper (80-100 grit).

- **Step 1:** Strip wood with #1 Deck Wood Stain Stripper and rinse thoroughly with a garden hose or pressure washer (max. 1200 PSI). #1 Deck Wood Stain Stripper is effective on weathered semi-transparent or clear stains.
- **Step 2:** Brighten wood with #1 Deck Wood Brightener and rinse thoroughly.

APPLICATION

Ensure surface temperature is between 45°F and 95°F. Avoid application of product when the daily low is below 45 or when rain is expected within 12 hours. **Do not apply in direct sunlight or if boards feel hot to touch.**

Damp Wood: #1 Deck Premium Fence Stain can be applied over damp wood surfaces following the cleaning process. Once cleaning is complete, allow the wood to dry for a couple of hours, until such time as the surface becomes visually dry, and then proceed with staining.

Mix Well: Stir well before and periodically during use. Do not dilute.

Protect Adjacent Areas: Use plastic, cardboard, and/or drop cloths to protect all adjacent non-target surfaces such as siding, windows, masonry, plant life, etc... from overspray/runoff. Immediately remove overspray from non-target areas with soap and water before it dries.

Equipment: Hand brushes should be high quality nylon or polyester. If using an airless sprayer, use tips between .011 and .015, and use the lowest pressure that achieves a uniform spray pattern to minimize fogging and overspray. When spraying, always back-brush. This ensures a uniform application, and breaks the surface tension of the wood for better penetration of the stain.

Apply stain to vertical fence boards using the method of your choice. A car-wash type brush (available in the automotive section of most hardware stores) is a great tool for back brushing. Apply the stain along the full length of the board starting at the bottom and work your way up. Never break in the middle of a board. Apply two wet-on-damp coats, waiting approximately 20-30 minutes between coats. Do not over-apply the stain. Back-brush product into surface, working out all drips before product dries. To avoid the possibility of peeling, only apply as much stain as the wood can absorb. Thoroughly coat the ends of boards to prevent water penetration.

Coverage: 100-150 sq. ft. per gallon (for 2 coats) depending on surface porosity & application method.

Dry Time: Stain will be dry to touch in 1-2 hours. A complete cure of the coating is 24 to 48 hours at 65° F and less than 50% humidity.

Maintenance: As the wood begins to look weathered or at the first signs of graying, clean the surface with #1 Deck Wood Brightener and then apply a single maintenance coat of #1 Deck Premium Fence Stain.

Cleanup: Clean tools immediately after each use with soap and water.

PRECAUTIONS

Keep out of reach of children. May cause an allergic skin reaction. Avoid breathing fumes, dust, mist, spray, vapors. Wear eye protection, protective clothing, and protective gloves. Dispose of contents/container to comply with applicable local, national and international regulation.

FIRST AID

IF INHALED: Move the affected person away from the contaminated area and into the fresh air. If symptoms persist, seek medical advice. **SKIN CONTACT:** Wash off immediately with soap and plenty of water. Obtain medical attention if irritation persists. **EYE CONTACT:** Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention if irritation persists. **INGESTION:** If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting unless directed to do so by a physician. If the person is fully conscious, make him/her drink water. Never give an unconscious person anything to drink. Immediately call a POISON CENTER or doctor/physician.

For additional information for this product, consult the Product Data Sheet or Safety Data Sheet available at www.1deck.com.

LIMITED 3 YEAR WARRANTY

SaverSystems warrants to the original residential consumer purchaser the performance of this product as described on this label for three (3) years on vertical surfaces, from the date of purchase, for so long as you reside in your home. This warranty is not valid when the product is not properly applied to a properly prepared surface or cared for in accordance with the label directions. Color fading and slight natural graying of the wood may occur during the warranty period, especially in areas exposed to excessive weather. This warranty is not transferable. This warranty does not cover pre-existent faulty construction and/or other defects which might erode treated surfaces. If stain fails to perform as specified, SaverSystems will furnish, as the sole remedy, enough product to correct the condition. This warranty does not include labor, or the cost of labor for the reapplication of stain. SaverSystems shall not be liable for incidental or consequential damages resulting from any breach of this warranty and fitness for use. Some states do not allow the exclusion of incidental or consequential damages, so the above exclusions may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

Shelf Life: 36 months

PACKAGING

Available in 1 and 2.5 gallon recyclable plastic containers.

TRANSPORT AND HANDLING

#1 Deck Premium Fence Stain is not considered hazardous under Department of Transportation regulations. Do not stack pallets. **Keep from freezing.**

PHYSICAL PROPERTIES

VOC CONTENT <50 g/L