

SECTION 1: Identification

1.1. Identification

Product name : #1 Deck Premium Wood Stain

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Exterior Wood Surface Stain.

1.3. Details of the supplier of the safety data sheet

SaverSystems
800 7th Street
Richmond, IN 47374
T 800-860-6327
www.saversystems.com

1.4. Emergency telephone number

Emergency number : ChemTel LLC
(800)255-3924 (North America)
+1 (813)248-0585 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin Sens. 1 H317

Full text of hazard classes and H-statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



GHS07

Signal word (GHS US) :

Warning

Hazard statements (GHS US) :

H317 - May cause an allergic skin reaction

Precautionary statements (GHS US) :

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 - If on skin: Wash with plenty of water.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

#1 Deck Premium Wood Stain

Safety Data Sheet

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Water	(CAS-No.) 7732-18-5	Trade Secret	Not classified
2-Propanol, 1-(2-butoxy-1-methylethoxy)-	(CAS-No.) 29911-28-2	Trade Secret	Not classified
3-Iodo-2-propynyl butylcarbamate	(CAS-No.) 55406-53-6	Trade Secret	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation), H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one	(CAS-No.) 64359-81-5	Trade Secret	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 1 (Inhalation), H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause an allergic skin reaction
Symptoms/effects after inhalation	: Prolonged exposure may cause irritation.
Symptoms/effects after skin contact	: May cause an allergic skin reaction
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: Ingestion may cause adverse effects.

4.3. Indication of any immediate medical attention and special treatment needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray, fog, carbon dioxide (CO2), alcohol-resistant foam, or dry chemical.
Unsuitable extinguishing media	: Do not use a heavy water stream as it may spread fire.

5.2. Special hazards arising from the substance or mixture

Reactivity	: Will not occur under normal conditions.
------------	---

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel. Do not breathe vapor, mist or spray. Do not get in eyes, on skin, or on clothing.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
----------------------	--

#1 Deck Premium Wood Stain

Safety Data Sheet

Emergency procedures : Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to other sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid breathing vapors, mist, spray. Avoid contact with skin, eyes and clothing.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep container closed when not in use. Store in a dry, cool place and away from direct sunlight, extremely high or low temperatures and incompatible materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Water (7732-18-5)

Not applicable

3-Iodo-2-propynyl butylcarbamate (55406-53-6)

Not applicable

4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one (64359-81-5)

Not applicable

2-Propanol, 1-(2-butoxy-1-methylethoxy)- (29911-28-2)

Not applicable

8.2. Exposure controls

Hand protection : Wear protective gloves.

Eye protection : Chemical safety goggles.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : If exposure limits are exceeded or irritation is experienced, use NIOSH approved respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Brown
Odor : Slight chemical odor
Odor threshold : No data available
pH : 8
Melting point : No data available
Freezing point : < 0 °C (32 °F)
Boiling point : > 100 °C (>212 °F)
Flash point : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : Non flammable.

#1 Deck Premium Wood Stain

Safety Data Sheet

Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 1.006 g/cm ³ (8.4 lb/gal)
Solubility	: Soluble
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Hazardous reactions will not occur under normal conditions.

10.2. Chemical stability

Stable under normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong oxidizers and reducing agents.

10.6. Hazardous decomposition products

Thermal decomposition may generate toxic vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Water (7732-18-5)	
LD50 oral rat	> 90 ml/kg
3-Iodo-2-propynyl butylcarbamate (55406-53-6)	
LD50 oral rat	1470 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	0.99 mg/l/4h
ATE US (oral)	1100 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h
4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one (64359-81-5)	
ATE US (oral)	500 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	10 ppmV/4h
ATE US (vapors)	0.05 mg/l/4h
ATE US (dust, mist)	0.005 mg/l/4h
2-Propanol, 1-(2-butoxy-1-methylethoxy)- (29911-28-2)	
LD50 oral rat	1620 µl/kg

#1 Deck Premium Wood Stain

Safety Data Sheet

2-Propanol, 1-(2-butoxy-1-methylethoxy)- (29911-28-2)

LC50 Inhalation - Rat [ppm]	42.1 ppm/4h
ATE US (gases)	42.1 ppmV/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

3-Iodo-2-propynyl butylcarbamate (55406-53-6)

LC50 - Fish [1]	0.14 – 0.32 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
LC50 - Fish [2]	0.049 – 0.079 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])

2-Propanol, 1-(2-butoxy-1-methylethoxy)- (29911-28-2)

LC50 - Fish [1]	841 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])
-----------------	--

12.2. Persistence and degradability

#1 Deck Premium Wood Stain

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

#1 Deck Premium Wood Stain

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT
Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Water (7732-18-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#1 Deck Premium Wood Stain

Safety Data Sheet

2-Propanol, 1-(2-butoxy-1-methylethoxy)- (29911-28-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State regulations

3-Iodo-2-propynyl butylcarbamate (55406-53-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Full text of H-phrases:

Acute Tox. 1 (Inhalation)	Acute toxicity (inhalation) Category 1
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Sens. 1	Skin sensitization, Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H330	Fatal if inhaled
H331	Toxic if inhaled
H335	May cause respiratory irritation
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.