HeatShield Adhesion Promoter

Product Data Sheet

MANUFACTURER:

CeCure Chimney Systems, LLC
C/O SaverSystems
Richmond, IN 47374
800-860-6327
Fax: 765-935-4999
www.heatshieldpro.com

DESCRIPTION

HeatShield Adhesion Promoter is a liquid additive that may be added to HeatShield Cerfractory Flue sealant or HeatShield Cerfractory Foam upon mixing to further promote adhesion or bonding to flue tiles and masonry surfaces. Because the interior surfaces of masonry chimneys and fireplaces are often difficult to clean and prep, the use of HeatShield Adhesion Promoter insures maximum bonding potential.

USES

HeatShield Adhesion Promoter is a clear, syrupy liquid that replaces a portion of the water used for mixing. It also improves strength by reducing the total amount of water required for application.

ADVANTAGES

- Insures Maximum Bonding Potential
- Improves Strength

DIRECTIONS FOR USE

Each gallon of Adhesion Promoter is adequate for mixing 5-50 lb. pails of HeatShield or 10-25 lb. pails of Cerfractory Foam.

MIXING INSTRUCTIONS

Follow mixing instructions for HeatShield Cerfractory Flue Sealant or Cerfractory Foam. For mixing 50lbs of HeatShield replace one liter of water initially added to mixing tub with 750ml (approximately 26 ounces) of Adhesion Promoter. For mixing 25lbs of HeatShield Cerfractory Foam replace ½ liter of water initially added to mixing tub with 325ml (approximately 13 ounces). Add HeatShield dry powder and mix for about 2 minutes until all material is wet. Let stand for 5-10 minutes.

Remix for a few minutes to a mortar like consistency. Add small amounts of water as needed and remix to desired consistency.

CLEAN UP

Thoroughly rinse spray equipment, mixing containers and tools with water immediately after use. Spilled material is very slippery. Promptly clean up inadvertent spills.

CAUTIONS

The use of chemical splash goggles and protective gloves are recommended when handling all chemical products. If spray mist is created, the use of a NIOSH approved respirator is recommended. Avoid contact with eyes, skin and clothing. Avoid breathing spray mist. Material causes severe irritation to eyes, moderate irritation to skin and spray mist is irritating to respiratory tract. California Proposition 65: This product may contain impurities/trace elements know to the State of California to cause cancer or reproductive toxicity.

FIRST AID

If inhaled: Ensure fresh air breathing. Keep person at rest in a position comfortable for breathing. Call a Poison Center or seek medical attention if you feel unwell.

If swallowed: Rinse mouth. If you feel unwell, contact a Poison Center or a doctor/physician

For skin contact: Wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. If skin irritation occurs, seek medical advice/attention.

For eye contact Immediately rinse eyes cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, seek medical advice/attention.

For additional information for this product, consult the Safety Data Sheet available at www.heatshieldpro.com.

PACKAGING

Available in one-gallon recyclable plastic containers.

TRANSPORT AND HANDLING

HeatShield Adhesion Promoter is not considered hazardous under department of Transportation (DOT) regulations. Store in original container only, protect from freezing and excessive heat. Keep container closed.

PHYSICAL PROPERTIES

COLOR . . . . . Colorless to slight tint
ODOR . . . . . Odorless to slight odor
DENSITY . . . . . 10.0 – 13.4 lb/gal
SHELF LIFE . . . . . 24 months when unopened

©2015 SaverSystems