

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : DEFY Marine Seal Semi-Transparent Wood Dock Stain & Sealer

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Exterior Wood Surface Stain.

1.3. Supplier

Manufacturer

SaverSystems
800 7th Street
Richmond, Indiana 47374
USA
T 800-860-6327
www.saversystems.com

1.4. Emergency telephone number

Emergency number : ChemTel LLC
(800)255-3924 (North America)
+1 (813)248-0585 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin sensitization, Category 1 H317 May cause an allergic skin reaction
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS) :



Signal word (GHS) : Warning
Hazard statements (GHS) : H317 - May cause an allergic skin reaction
Precautionary statements (GHS) : P261 - Avoid breathing mist, spray, vapors.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 - If on skin: Wash with plenty of water.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

DEFY Marine Seal Semi-Transparent Wood Dock Stain & Sealer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown acute toxicity (GHS)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	CAS-No.: 41556-26-7	0.1-0.5	Flam. Liq. 4, H227 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

If exposed or concerned: Get medical advice/attention.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Reactivity in case of fire	: Stable under normal conditions.
----------------------------	-----------------------------------

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

DEFY Marine Seal Semi-Transparent Wood Dock Stain & Sealer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up immediately. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). This material and its container must be disposed of in a safe way, and as per local legislation. Notify environmental authorities.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mist, spray, vapors.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight. Incompatible materials. Keep container closed when not in use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DEFY Marine Seal Semi-Transparent Wood Dock Stain & Sealer

No additional information available

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)

No additional information available

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

DEFY Marine Seal Semi-Transparent Wood Dock Stain & Sealer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hand protection:
Wear protective gloves.
Eye protection:
Chemical goggles or face shield
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
If excessive exposure exists, use only approved air-purifying or supplied air respirator operated in a positive pressure mode

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Colorless liquid.
Color	: Colorless
Odor	: characteristic
Odor threshold	: No data available
pH	: 8
Melting point	: No data available
Freezing point	: < 0 °C
Boiling point	: > 100 °C
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.006
Solubility	: Soluble.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

DEFY Marine Seal Semi-Transparent Wood Dock Stain & Sealer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

Under normal conditions of storage and use, hazardous reactions will not occur.

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong oxidizers. Reducing agents.

10.6. Hazardous decomposition products

Thermal decomposition generates : Corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)

LD50 Oral rat	2369 (2369 – 3920) mg/kg
ATE (oral)	2369 mg/kg body weight

Skin corrosion/irritation : Not classified
pH: 8
Serious eye damage/irritation : Not classified
pH: 8
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available
Likely routes of exposure : Inhalation. Skin and eye contact.

SECTION 12: Ecological information

12.1. Toxicity

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)

LC50 fish 1	0.97 mg/l 96 h
-------------	----------------

DEFY Marine Seal Semi-Transparent Wood Dock Stain & Sealer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)	
EC50 crustacea	20 mg/l 24 h

12.2. Persistence and degradability

DEFY Marine Seal Semi-Transparent Wood Dock Stain & Sealer	
Persistence and degradability	Not established.

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)	
Biodegradation	38 % 28 d

12.3. Bioaccumulative potential

DEFY Marine Seal Semi-Transparent Wood Dock Stain & Sealer	
Bioaccumulative potential	Not established.

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)	
Log Pow	0.37

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable

DEFY Marine Seal Semi-Transparent Wood Dock Stain & Sealer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

United States Environmental Protection Agency Toxic Substances Control Act (TSCA): Consult the supplier for further information

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)
Listed on Taiwan National Chemical Inventory
Listed on the Inventory of Existing Chemical Substances Produced or Imported in China (IECSC).
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

15.3. US State regulations

WARNING:

Warning: This product can expose you to Ethylene oxide, which is known to the State of California to cause birth defects or other reproductive harm, and Cumene, which is known to the State of California to cause cancer. For more information, go to www.p65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 12/03/2021

Other information : None.

DEFY Marine Seal Semi-Transparent Wood Dock Stain & Sealer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H227	Combustible liquid
H317	May cause an allergic skin reaction
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.